



REDLINE 12-80 V DC

Červené svetlo pre označenie

EEW2015R
ECCO Red line 12-80 V



- 360 ° výstražná indikácia
- Extrémne odolné proti nárazom a vibráciám
- Polykarbonátová šošovka
- Hliníkové puzdro



POPIS PRODUKTU

ŠPECIFIKÁCIA

Battery	Nie
Color light	Červená
EMC	R10
Farba	Číra
Hmotnosť	0,27 kg
Materiál	Hliník
Number of LED	3 ks
Prevádzková teplota max.	50 °C
Prevádzková teplota min.	-30 °C
Šírka	62 mm
Svätelný tok	86 lm
Typ zdroja	Červená LED
Voltage	12-80V
Výška	65 mm
Width base	74 mm

REVISIONS	
REV.	DESCRIPTION
1	REWORK REQUIRED (REVISED)
2	REWORK REQUIRED (REVISED)
3	REWORK REQUIRED (REVISED)

SPECIFICATIONS

1. OPERATIONAL LIFE: 50,000 Hrs. (C-Risk)
- Note: Unique components, accessories, and hardware are pre-qualified and included in the Product Certification Test Protocol. Other materials supplied by the Buyer. Certifications related to these are published upon the Buyer's request.
2. RAW LUMENS: 84 lumens
3. EFFECTIVE LUMENS: 63 lumens
4. LUMINANCE: 7.6 lm
5. BEAM ANGLE: 143° CANSIM
6. EFFICACY: 18.8 lm/W
7. CORRELATED COLOR TEMPERATURE: 1000K
8. VOLTAGE (NOMINAL): 12 to 18 VDC
9. VOLTAGE (EXTREME): 9.0 to 18.0 VDC
10. CURRENT (TYPICAL): 150 mA @ 12 VDC (NOMINAL)
11. POWER (MAXIMUM): 1.32 W @ 12 VDC (NOMINAL)
12. TEMPERATURE RANGE: -20°C (-4°F) TO 120°C (248°F)
13. CONNECTION: 2 - 18 AWG WIRE CABLE
14. HOUSING: BRACKET MOUNT
15. HOUSING MATERIAL: ALUMINUM
16. LENS MATERIAL: POLYCARBONATE
17. PRODUCT WEIGHT: 0.4181 (0.27 kg)

DISCLAIMER
DIMENSIONAL ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS COVERED BY THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. EDDO ENGINEERING DOES NOT WARRANT FORMAL DESIGN CONTROL OF THE PRODUCT.

MOUNTING DISCLAIMER
MOUNTING MEASUREMENTS FOR REFERENCE ONLY. MEASURE BEFORE CALLING.

REVISIONS	
REV.	DESCRIPTION
1	REWORK REQUIRED (REVISED)
2	REWORK REQUIRED (REVISED)
3	REWORK REQUIRED (REVISED)

NOTES

1. ESDS COMPLIANT
2. DIMENSIONS IN PARENTHESIS (FOR REFERENCE)

www.eddo.com
WORLDWIDE LED LINE 12-18V RED
E00015

REVISIONS	
REV.	DESCRIPTION
1	REWORK REQUIRED (REVISED)
2	REWORK REQUIRED (REVISED)
3	REWORK REQUIRED (REVISED)

SPECIFICATIONS

1. OPERATIONAL LIFE: 50,000 Hrs. (C-Risk)
- Note: Unique components, accessories, and hardware are pre-qualified and included in the Product Certification Test Protocol. Other materials supplied by the Buyer. Certifications related to these are published upon the Buyer's request.
2. RAW LUMENS: 84 lumens
3. EFFECTIVE LUMENS: 63 lumens
4. LUMINANCE: 7.6 lm
5. BEAM ANGLE: 143° CANSIM
6. EFFICACY: 18.8 lm/W
7. CORRELATED COLOR TEMPERATURE: 1000K
8. VOLTAGE (NOMINAL): 12 to 18 VDC
9. VOLTAGE (EXTREME): 9.0 to 18.0 VDC
10. CURRENT (TYPICAL): 150 mA @ 12 VDC (NOMINAL)
11. POWER (MAXIMUM): 1.32 W @ 12 VDC (NOMINAL)
12. TEMPERATURE RANGE: -20°C (-4°F) TO 120°C (248°F)
13. CONNECTION: 2 - 18 AWG WIRE CABLE
14. HOUSING: BRACKET MOUNT
15. HOUSING MATERIAL: ALUMINUM
16. LENS MATERIAL: POLYCARBONATE
17. PRODUCT WEIGHT: 0.4181 (0.27 kg)

DISCLAIMER
DIMENSIONAL ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS COVERED BY THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. EDDO ENGINEERING DOES NOT WARRANT FORMAL DESIGN CONTROL OF THE PRODUCT.

MOUNTING DISCLAIMER
MOUNTING MEASUREMENTS FOR REFERENCE ONLY. MEASURE BEFORE CALLING.

REVISIONS	
REV.	DESCRIPTION
1	REWORK REQUIRED (REVISED)
2	REWORK REQUIRED (REVISED)
3	REWORK REQUIRED (REVISED)

NOTES

1. ESDS COMPLIANT
2. DIMENSIONS IN PARENTHESIS (FOR REFERENCE)

www.eddo.com
WORLDWIDE LED LINE 12-18V RED
E00015