Dopyt

REDLINE 12-80 V DC

Červené svetlo pre označenie

EEW2015R
ECCO Red line 12-80 V




- 360 ° výstražná indikácia
- Extrémne odolné proti nárazom a vibráciám
- Polykarbonátová šošovka
- Hliníkové puzdro

POPIS PRODUKTU

ŠPECIFIKÁCIA

Battery	Nie
Color light	Červená
EMC	R10
Farba	Číra
Hmotnosť	0,27 kg
Materiál	Hliník
Number of LED	3 ks
Prevádzková teplota max.	50 °C
Prevádzková teplota min.	-30 °C
Šírka	62 mm
Světelný tok	86 lm
Typ zdroja	Červená LED
Voltage	12-80V
Výška	65 mm
Width base	74 mm



REVISIONS		
REV	DESCRIPTION	DATE
C	RELEASED PER ECO77	2017-08
B	INITIAL RELEASE PER ECO77	2017-04
A	RELEASE PER ECO77	2017-04

SPECIFICATIONS

1. CERTIFICATIONS: ECE R10; C-Tick ;
   Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
2. RAW LUMENS: 86 lumens
3. EFFECTIVE LUMENS: 65 lumens
4. ILLUMINANCE: 1.6 lux
5. PEAK BEAM INTENSITY: 1433 Candela
6. EFFICACY: 16.5 lm/W
7. CORRELATED COLOR TEMPERATURE: 1000K
8. VOLTAGE (NOMINAL): 12 to 80 VDC
9. VOLTAGE (EXTREME): 9.0 to 86.0 VDC
10. CURRENT (PEAK): 1.03A (@ 12 VDC NOMINAL)
11. POWER (MAXIMUM): 13.2W (@ 12 VDC NOMINAL)
12. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
13. CONNECTION: 2 - 18 AWG WIRE CABLE
14. MOUNTING: BRACKET MOUNT
15. HOUSING MATERIAL: ALUMINUM
16. LENS MATERIAL: POLYCARBONATE
17. PRODUCT WEIGHT: 0.6 LBS (0.27 Kg)

DISCLAIMER
DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

MOUNTING DISCLAIMER
MOUNTING MEASUREMENT IS FOR REFERENCE ONLY. MEASURE BEFORE DRILLING.

NOTES:
1. ROHS COMPLIANT
2. DIMENSIONS IN INCHES [MILLIMETERS (FOR REFERENCE)]


DRAWN	DATE
[illegible]	2017/05/05
[illegible]	2017/05/05
[illegible]	2017/05/05
[illegible]	2017/05/05
[illegible]	2017/05/07
[illegible]	2017/05/04

www.eccolink.com

WORKLAMP LED LINE 12-80V RED

SIZE	DWG. NO	REV
A	EW2015R	B

SCALE	WEIGHT	SHEET
1:1	0.6 LBS	1 OF 1



REVISIONS		
REV	DESCRIPTION	DATE
C	RELEASED PER ECO77	2017-08
B	INITIAL RELEASE PER ECO77	2017-04
A	RELEASE PER ECO77	2017-04

SPECIFICATIONS

1. CERTIFICATIONS: ECE R10; C-Tick ;
   Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
2. RAW LUMENS: 86 lumens
3. EFFECTIVE LUMENS: 65 lumens
4. ILLUMINANCE: 1.6 lux
5. PEAK BEAM INTENSITY: 1433 Candela
6. EFFICACY: 16.5 lm/W
7. CORRELATED COLOR TEMPERATURE: 1000K
8. VOLTAGE (NOMINAL): 12 to 80 VDC
9. VOLTAGE (EXTREME): 9.0 to 86.0 VDC
10. CURRENT (PEAK): 1.03A (@ 12 VDC NOMINAL)
11. POWER (MAXIMUM): 13.2W (@ 12 VDC NOMINAL)
12. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
13. CONNECTION: 2 - 18 AWG WIRE CABLE
14. MOUNTING: BRACKET MOUNT
15. HOUSING MATERIAL: ALUMINUM
16. LENS MATERIAL: POLYCARBONATE
17. PRODUCT WEIGHT: 0.6 LBS (0.27 Kg)

DISCLAIMER
DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

MOUNTING DISCLAIMER
MOUNTING MEASUREMENT IS FOR REFERENCE ONLY. MEASURE BEFORE DRILLING.

NOTES:
1. ROHS COMPLIANT
2. DIMENSIONS IN INCHES [MILLIMETERS (FOR REFERENCE)]

DRAWN	DATE
[illegible]	2017/05/05
[illegible]	2017/05/05
[illegible]	2017/05/05
[illegible]	2017/05/05
[illegible]	2017/05/07
[illegible]	2017/05/04

www.eccolink.com

WORKLAMP LED LINE 12-80V RED

SIZE	DWG. NO	REV
A	EW2015R	B

SCALE	WEIGHT	SHEET
1:1	0.6 LBS	1 OF 1