



Dopyt



JÍMKY

Série TW45

TW45F-3244334

Jímka 10x8x0,9mm G1/2 G1/2F L=82mm

- Materiál nerez
- Připojení G



POPIS PRODUKTU

ŠPECIFIKÁCIA

Insertion length 82 mm


Inside diameter 8 mm

Materiál Nerezová ocel'

Priemer 10 mm


Thickness 0,9 mm

Dimensions in mm




Material	Dimensions in mm										Weight in kg		
	E	N	Ø d1	Ø d2	H1	H2	K1	S	S1	SW	U1 ± 0.2 mm	U1 ± 382 mm	
Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	19	15	14	2.5	3.5	27	0.15	0.33
	G 1/2	G 1/2	9	26	14	19	15	14	2.5	3.5	27	0.15	0.36
	G 1/2	G 1/2	11	26	14	19	15	14	1.5	2.5	27	0.12	0.28
	G 1/2	G 1/2	6.2	26	8	19	15	14	0.9	1	27	0.12	0.18
	G 1/2	G 1/2	8.2	26	10	19	15	14	0.9	1	27	0.12	0.18
	G 1/2	G 1/2	10.2	26	12	19	15	14	0.9	1	27	0.12	0.18
	G 1/2	G 1/2	7	32	12	19	15	16	2.5	3.5	32	0.24	0.42
	G 1/2	G 1/2	9	32	14	19	15	16	2.5	3.5	32	0.24	0.45
	G 1/2	G 1/2	11	32	14	19	15	16	1.5	2.5	32	0.22	0.37
	G 1/2	G 1/2	6.2	32	8	19	15	16	0.9	1	32	0.21	0.27
	G 1/2	G 1/2	8.2	32	10	19	15	16	0.9	1	32	0.21	0.27
	G 1/2	G 1/2	10.2	32	12	19	15	16	0.9	1	32	0.21	0.27
	G 1/2	G 1/2	7	32	12	22	17	16	2.5	3.5	32	0.20	0.38
	G 1/2	G 1/2	9	32	14	22	17	16	2.5	3.5	32	0.20	0.41
	G 1/2	G 1/2	11	32	14	22	17	16	1.5	2.5	32	0.18	0.33
	G 1/2	G 1/2	6.2	32	8	22	17	16	0.9	1	32	0.17	0.23
Copper	G 1/2	G 1/2	8.5	32	10	22	17	16	0.9	1	32	0.17	0.23
	G 1/2	G 1/2	10.5	32	12	22	17	16	0.9	1	32	0.17	0.23
	G 1/2	G 1/2	6.2	26	10	19	15	14	0.75	0.75	27	0.11	0.18

Model TW45-G




Material	Dimensions in mm										Weight in kg	
	E	N	Ø d1	Ø d2	H1	K1	K2	S	S1	SW	U1 ± 72 mm	U1 ± 410 mm
Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	14	12	2.5	3.5	27	0.14	0.34
	G 1/2	G 1/2	9	26	14	14	12	2.5	3.5	27	0.14	0.37
	G 1/2	G 1/2	11	26	14	14	12	1.5	2.5	27	0.12	0.30
	G 1/2	G 1/2	6.2	26	8	12	14	0.9	1	27	0.13	0.20
	G 1/2	G 1/2	8.2	26	10	14	12	0.9	1	27	0.13	0.20
	G 1/2	G 1/2	10.2	26	12	14	12	0.9	1	27	0.13	0.18
	G 1/2	G 1/2	7	32	12	16	14	2.5	3.5	32	0.22	0.43
	G 1/2	G 1/2	9	32	14	16	14	2.5	3.5	32	0.22	0.46
	G 1/2	G 1/2	11	32	14	16	14	1.5	2.5	32	0.20	0.38
	G 1/2	G 1/2	6.2	32	8	16	14	0.9	1	32	0.21	0.28
	G 1/2	G 1/2	8.2	32	10	16	14	0.9	1	32	0.21	0.28
	G 1/2	G 1/2	10.2	32	12	16	14	0.9	1	32	0.21	0.27

Dimensions in mm



Material	Dimensions in mm										Weight in kg		
	E	N	Ø d1	Ø d2	H1	H2	K1	S	S1	SW	U1 ± 0.2 mm	U1 ± 382 mm	
Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	19	15	14	2.5	3.5	27	0.15	0.33
	G 1/2	G 1/2	9	26	14	19	15	14	2.5	3.5	27	0.15	0.36
	G 1/2	G 1/2	11	26	14	19	15	14	1.5	2.5	27	0.12	0.28
	G 1/2	G 1/2	6.2	26	8	19	15	14	0.9	1	27	0.12	0.18
	G 1/2	G 1/2	8.2	26	10	19	15	14	0.9	1	27	0.12	0.18
	G 1/2	G 1/2	10.2	26	12	19	15	14	0.9	1	27	0.12	0.18
	G 1/2	G 1/2	7	32	12	19	15	16	2.5	3.5	32	0.24	0.42
	G 1/2	G 1/2	9	32	14	19	15	16	2.5	3.5	32	0.24	0.45
	G 1/2	G 1/2	11	32	14	19	15	16	1.5	2.5	32	0.22	0.37
	G 1/2	G 1/2	6.2	32	8	19	15	16	0.9	1	32	0.21	0.27
	G 1/2	G 1/2	8.2	32	10	19	15	16	0.9	1	32	0.21	0.27
	G 1/2	G 1/2	10.2	32	12	19	15	16	0.9	1	32	0.21	0.27
Copper	G 1/2	G 1/2	7	32	12	22	17	16	2.5	3.5	32	0.20	0.38
	G 1/2	G 1/2	9	32	14	22	17	16	2.5	3.5	32	0.20	0.41
	G 1/2	G 1/2	11	32	14	22	17	16	1.5	2.5	32	0.18	0.33
	G 1/2	G 1/2	6.2	32	8	22	17	16	0.9	1	32	0.17	0.23
	G 1/2	G 1/2	8.2	32	10	22	17	16	0.9	1	32	0.17	0.23
	G 1/2	G 1/2	10.2	32	12	22	17	16	0.9	1	32	0.17	0.23
	G 1/2	G 1/2	7	32	12	22	17	16	2.5	3.5	32	0.20	0.38
	G 1/2	G 1/2	9	32	14	22	17	16	2.5	3.5	32	0.20	0.41
	G 1/2	G 1/2	11	32	14	22	17	16	1.5	2.5	32	0.18	0.33
	G 1/2	G 1/2	6.2	32	8	22	17	16	0.9	1	32	0.17	0.23
	G 1/2	G 1/2	8.5	26	10	19	15	14	0.75	0.75	27	0.11	0.18
	G 1/2	G 1/2	10.5	26	12	19	15	14	0.75	0.75	27	0.11	0.18

Model TW45-G



Material	Dimensions in mm										Weight in kg	
	E	N	QD1	QD2	QF1	K1	K2	S	S1	Sw	U1 x 12 mm	U1 x 410 mm
Stainless steel 1.4571	G 1/8	G 1/8	7	26	12	14	12	2.5	3.5	27	0.14	0.34
	G 1/8	G 1/8	9	26	14	14	12	2.5	3.5	27	0.14	0.37
G 1/8	G 1/8	11	26	14	14	12	1.5	2.5	27	0.12	0.30	
G 1/8	G 1/8	6.2	26	8	14	12	0.9	1	27	0.13	0.20	
G 1/8	G 1/8	8.2	26	10	14	12	0.9	1	27	0.13	0.20	
G 1/8	G 1/8	10.2	26	12	14	12	0.9	1	27	0.11	0.18	
G 1/8	G 1/8	7	32	12	16	14	2.5	3.5	32	0.22	0.43	
G 1/8	G 1/8	9	32	14	16	14	2.5	3.5	32	0.22	0.46	
G 1/8	G 1/8	11	32	14	16	14	1.5	2.5	32	0.20	0.39	
G 1/8	G 1/8	6.2	32	8	16	14	0.9	1	32	0.21	0.29	
G 1/8	G 1/8	8.2	32	10	16	14	0.9	1	32	0.21	0.28	
G 1/8	G 1/8	10.2	32	12	16	14	0.9	1	32	0.20	0.27	