



Dopyt



TERMOČLÁNKY

Séria TC47-AB

TC47-AB
Termočlánok

- Teplota -40°C až 750°C
- K, J, K, T
- Telo nerez



POPIS PRODUKTU

ŠPECIFIKÁCIA

Prevádzková teplota max.

750 °C

Prevádzková teplota min.

-40 °C

Adjustable bayonet - Spring up to 200 mm or 8" of adjustability - Armour full lead length of adjustability Junction - Grounded (unisolated) - Ungrounded (isolated) Tip diameter (Ø) 3/16" 1/4" 3/8" 4 mm 6 mm 8 mm 10 mm - Others on request Probe length - Standard - Others on request	 Lead wire - Fibreglass / fibreglass - PTFE / PTFE - PVC / PVC - Kapton / Kapton - Others on request Lead wire covering - None - Stainless steel overbraid (no tracer) - Stainless steel overbraid (with tracer) - Tin copper overbraid - Interlocking flexible armour Termination at lead end - Bare ends - Standard thermo plug 2-pin (male) - Miniature thermo plug 2-pin (male) - Standard plug with cable clamp (male) - Miniature plug with cable clamp (male) - Lemosa plug size 15 (male) - Lemosa plug size 25 (male) - Screw-in plug, Binder (male) - Others on request																																																			
Bayonet cap Id Ø Fits bayonet adapter <table> <tr> <td>Single slot</td><td>11.4 mm (7/16")</td><td>11 mm O.D.</td></tr> <tr> <td>Double slot</td><td>15.4 mm (7/16")</td><td>11 mm O.D.</td></tr> <tr> <td>Double slot</td><td>12.2 mm (3/16")</td><td>12 mm O.D.</td></tr> <tr> <td>Double slot</td><td>14.2 mm (9/16")</td><td>12 mm O.D.</td></tr> <tr> <td>Double slot</td><td>15.2 mm (19/32")</td><td>15 mm O.D.</td></tr> </table> - Others on request Lead length 500 mm 1000 mm 1500 mm 2000 mm 2500 mm - Others on request	Single slot	11.4 mm (7/16")	11 mm O.D.	Double slot	15.4 mm (7/16")	11 mm O.D.	Double slot	12.2 mm (3/16")	12 mm O.D.	Double slot	14.2 mm (9/16")	12 mm O.D.	Double slot	15.2 mm (19/32")	15 mm O.D.	 Calibration type <table> <tr> <td>J</td><td>ANSI MC96.1</td><td>red Ø</td><td>white Ø</td></tr> <tr> <td>K</td><td>ANSI MC96.1</td><td>red Ø</td><td>yellow Ø</td></tr> <tr> <td>T</td><td>ANSI MC96.1</td><td>red Ø</td><td>blue Ø</td></tr> <tr> <td>J</td><td>IEC 584-3</td><td>white Ø</td><td>black Ø</td></tr> <tr> <td>K</td><td>IEC 584-3</td><td>white Ø</td><td>green Ø</td></tr> <tr> <td>T</td><td>IEC 584-3</td><td>white Ø</td><td>brown Ø</td></tr> <tr> <td>J</td><td>DIN 43714</td><td>blue Ø</td><td>red Ø</td></tr> <tr> <td>K</td><td>DIN 43714</td><td>green Ø</td><td>red Ø</td></tr> <tr> <td>T</td><td>DIN 43714</td><td>brown Ø</td><td>red Ø</td></tr> </table> Others on request	J	ANSI MC96.1	red Ø	white Ø	K	ANSI MC96.1	red Ø	yellow Ø	T	ANSI MC96.1	red Ø	blue Ø	J	IEC 584-3	white Ø	black Ø	K	IEC 584-3	white Ø	green Ø	T	IEC 584-3	white Ø	brown Ø	J	DIN 43714	blue Ø	red Ø	K	DIN 43714	green Ø	red Ø	T	DIN 43714	brown Ø	red Ø
Single slot	11.4 mm (7/16")	11 mm O.D.																																																		
Double slot	15.4 mm (7/16")	11 mm O.D.																																																		
Double slot	12.2 mm (3/16")	12 mm O.D.																																																		
Double slot	14.2 mm (9/16")	12 mm O.D.																																																		
Double slot	15.2 mm (19/32")	15 mm O.D.																																																		
J	ANSI MC96.1	red Ø	white Ø																																																	
K	ANSI MC96.1	red Ø	yellow Ø																																																	
T	ANSI MC96.1	red Ø	blue Ø																																																	
J	IEC 584-3	white Ø	black Ø																																																	
K	IEC 584-3	white Ø	green Ø																																																	
T	IEC 584-3	white Ø	brown Ø																																																	
J	DIN 43714	blue Ø	red Ø																																																	
K	DIN 43714	green Ø	red Ø																																																	
T	DIN 43714	brown Ø	red Ø																																																	

Adjustable bayonet - Spring up to 200 mm or 8" of adjustability - Armour full lead length of adjustability	Lead wire - Fibreglass / fibreglass - PTFE / PTFE - PVC / PVC - Kapton / Kapton - Others on request																											
Junction - Grounded (unisolated) - Ungrounded (isolated)	Lead wire covering - None - Stainless steel overbraid (no tracer) - Stainless steel overbraid (with tracer) - Tin copper overbraid - Interlocking flexible armour																											
Tip diameter (Ø) 3/16" 1/4" 3/8" 4 mm 6 mm 8 mm 10 mm - Others on request	Termination at lead end - Bare ends - Standard thermo plug 2-pin (male) - Miniature thermo plug 2-pin (male) - Standard plug with cable clamp (male) - Miniature plug with cable clamp (male) - Lemosa plug size 15 (male) - Lemosa plug size 25 (male) - Screw-in plug, Binder (male) - Others on request																											
Probe length - Standard - Others on request																												
Bayonet cap Id Ø Fits bayonet adapter <table border="1"> <tr> <td>Single slot</td> <td>11.4 mm (7/16")</td> <td>11 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>11.4 mm (7/16")</td> <td>11 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>12.2 mm (3/16")</td> <td>12 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>14.2 mm (9/16")</td> <td>12 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>15.2 mm (19/32")</td> <td>15 mm O.D.</td> </tr> </table> Others on request	Single slot	11.4 mm (7/16")	11 mm O.D.	Double slot	11.4 mm (7/16")	11 mm O.D.	Double slot	12.2 mm (3/16")	12 mm O.D.	Double slot	14.2 mm (9/16")	12 mm O.D.	Double slot	15.2 mm (19/32")	15 mm O.D.													
Single slot	11.4 mm (7/16")	11 mm O.D.																										
Double slot	11.4 mm (7/16")	11 mm O.D.																										
Double slot	12.2 mm (3/16")	12 mm O.D.																										
Double slot	14.2 mm (9/16")	12 mm O.D.																										
Double slot	15.2 mm (19/32")	15 mm O.D.																										
Lead length 500 mm 1000 mm 1500 mm 2000 mm 2500 mm - Others on request																												
	Calibration type <table border="1"> <tr> <td>J ANSI MC96.1</td> <td>red Ø</td> <td>white Ø</td> </tr> <tr> <td>K ANSI MC96.1</td> <td>red Ø</td> <td>yellow Ø</td> </tr> <tr> <td>T ANSI MC96.1</td> <td>red Ø</td> <td>blue Ø</td> </tr> <tr> <td>J IEC 584-3</td> <td>white Ø</td> <td>black Ø</td> </tr> <tr> <td>K IEC 584-3</td> <td>white Ø</td> <td>green Ø</td> </tr> <tr> <td>T IEC 584-3</td> <td>white Ø</td> <td>brown Ø</td> </tr> <tr> <td>J DIN 43714</td> <td>blue Ø</td> <td>red Ø</td> </tr> <tr> <td>K DIN 43714</td> <td>green Ø</td> <td>red Ø</td> </tr> <tr> <td>T DIN 43714</td> <td>brown Ø</td> <td>red Ø</td> </tr> </table> Others on request	J ANSI MC96.1	red Ø	white Ø	K ANSI MC96.1	red Ø	yellow Ø	T ANSI MC96.1	red Ø	blue Ø	J IEC 584-3	white Ø	black Ø	K IEC 584-3	white Ø	green Ø	T IEC 584-3	white Ø	brown Ø	J DIN 43714	blue Ø	red Ø	K DIN 43714	green Ø	red Ø	T DIN 43714	brown Ø	red Ø
J ANSI MC96.1	red Ø	white Ø																										
K ANSI MC96.1	red Ø	yellow Ø																										
T ANSI MC96.1	red Ø	blue Ø																										
J IEC 584-3	white Ø	black Ø																										
K IEC 584-3	white Ø	green Ø																										
T IEC 584-3	white Ø	brown Ø																										
J DIN 43714	blue Ø	red Ø																										
K DIN 43714	green Ø	red Ø																										
T DIN 43714	brown Ø	red Ø																										