



Dopyt



TERMOČLÁNKY

Séria TC47-MT

TC47-MT
Termoclánok

- Teplota -40°C až 750°C
- K, J, K, T
- Telo nerez



POPIS PRODUKTU

ŠPECIFIKÁCIA

Prevádzková teplota max.

750 °C

Prevádzková teplota min.

-40 °C

Manifold block - Stainless steel - Others on request	Lead wire covering - None - Stainless steel overbraid (no tracer) - Stainless steel overbraid (with tracer) - Tin copper overbraid - Interlocking flexible armour																																								
Junction - Grounded (unisolated) - Ungrounded (isolated)	Termination at lead end - Bare ends  - Standard thermo plug 2-pin (male)  - Miniature thermo plug 2-pin (male)  - Standard plug with cable clamp (male)  - Miniature plug with cable clamp (male)  - Lemosa plug size 15 (male)  - Lemosa plug size 25 (male)  - Screw-in plug, Binder (male)  - Others on request																																								
Tip diameter (Ø) 4 mm  - Others on request																																									
Tip length 12 mm  20 mm  25 mm  - Others on request																																									
Lead length 500 mm  1000 mm  1500 mm  2000 mm  2500 mm  - Others on request																																									
Lead wire - Fiberglass / Fiberglass - PTFE / PTFE - PVC / PVC - Kapton / Kapton - Others on request	Calibration type <table><tr><td>J</td><td>ANSI MC96.1</td><td>red Ø</td><td>white Ø</td></tr><tr><td>F</td><td>ANSI MC96.1</td><td>red Ø</td><td>yellow Ø</td></tr><tr><td>T</td><td>ANSI MC96.1</td><td>red Ø</td><td>blue Ø</td></tr><tr><td>J</td><td>IEC 584-3</td><td>white Ø</td><td>black Ø</td></tr><tr><td>K</td><td>IEC 584-3</td><td>white Ø</td><td>green Ø</td></tr><tr><td>T</td><td>IEC 584-3</td><td>white Ø</td><td>brown Ø</td></tr><tr><td>J</td><td>DIN 43714</td><td>blue Ø</td><td>red Ø</td></tr><tr><td>K</td><td>DIN 43714</td><td>green Ø</td><td>red Ø</td></tr><tr><td>T</td><td>DIN 43714</td><td>brown Ø</td><td>red Ø</td></tr><tr><td colspan="4">Others on request</td></tr></table>	J	ANSI MC96.1	red Ø	white Ø	F	ANSI MC96.1	red Ø	yellow Ø	T	ANSI MC96.1	red Ø	blue Ø	J	IEC 584-3	white Ø	black Ø	K	IEC 584-3	white Ø	green Ø	T	IEC 584-3	white Ø	brown Ø	J	DIN 43714	blue Ø	red Ø	K	DIN 43714	green Ø	red Ø	T	DIN 43714	brown Ø	red Ø	Others on request			
J	ANSI MC96.1	red Ø	white Ø																																						
F	ANSI MC96.1	red Ø	yellow Ø																																						
T	ANSI MC96.1	red Ø	blue Ø																																						
J	IEC 584-3	white Ø	black Ø																																						
K	IEC 584-3	white Ø	green Ø																																						
T	IEC 584-3	white Ø	brown Ø																																						
J	DIN 43714	blue Ø	red Ø																																						
K	DIN 43714	green Ø	red Ø																																						
T	DIN 43714	brown Ø	red Ø																																						
Others on request																																									

Manifold block ■ Stainless steel ■ Others on request		Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour																																								
Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)		Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male)																																								
Tip diameter (Ø) ■ 4 mm ■ Others on request																																										
Tip length ■ 12 mm ■ 20 mm ■ 25 mm ■ Others on request																																										
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request																																										
Lead wire ■ Fiberglass / Fiberglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request																																										
Lead wire ■ Fiberglass / Fiberglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request		Calibration type <table><tr><td>J</td><td>ANSI MC96.1</td><td>red Ø</td><td>white Ø</td></tr><tr><td>K</td><td>ANSI MC96.1</td><td>red Ø</td><td>yellow Ø</td></tr><tr><td>T</td><td>ANSI MC96.1</td><td>red Ø</td><td>blue Ø</td></tr><tr><td>J</td><td>IEC 584-3</td><td>white Ø</td><td>black Ø</td></tr><tr><td>K</td><td>IEC 584-3</td><td>white Ø</td><td>green Ø</td></tr><tr><td>T</td><td>IEC 584-3</td><td>white Ø</td><td>brown Ø</td></tr><tr><td>J</td><td>DIN 43714</td><td>blue Ø</td><td>red Ø</td></tr><tr><td>K</td><td>DIN 43714</td><td>green Ø</td><td>red Ø</td></tr><tr><td>T</td><td>DIN 43714</td><td>brown Ø</td><td>red Ø</td></tr><tr><td colspan="4">■ Others on request</td></tr></table>	J	ANSI MC96.1	red Ø	white Ø	K	ANSI MC96.1	red Ø	yellow Ø	T	ANSI MC96.1	red Ø	blue Ø	J	IEC 584-3	white Ø	black Ø	K	IEC 584-3	white Ø	green Ø	T	IEC 584-3	white Ø	brown Ø	J	DIN 43714	blue Ø	red Ø	K	DIN 43714	green Ø	red Ø	T	DIN 43714	brown Ø	red Ø	■ Others on request			
J	ANSI MC96.1	red Ø	white Ø																																							
K	ANSI MC96.1	red Ø	yellow Ø																																							
T	ANSI MC96.1	red Ø	blue Ø																																							
J	IEC 584-3	white Ø	black Ø																																							
K	IEC 584-3	white Ø	green Ø																																							
T	IEC 584-3	white Ø	brown Ø																																							
J	DIN 43714	blue Ø	red Ø																																							
K	DIN 43714	green Ø	red Ø																																							
T	DIN 43714	brown Ø	red Ø																																							
■ Others on request																																										