



Dopyt

TERMOMETRE

Séria IFC

IFC-14349092

Termometer Ø60, 0-120°C, L=1m, slät 50x8mm



- Expanzné
- Teplota -40°C až 400°C
- Ø60, Ø80, Ø100 mm
- Kapilára






POPIS PRODUKTU


ŠPECIFIKÁCIA

Capillary length	1000 mm
Insertion length	50 mm
Materiál kontaktnej časti	Mosadz
Materiál skla	Inertný plyn
Materiál tela	Plast
Plug diameter	8 mm
Prevádzková teplota max.	120 °C
Prevádzková teplota min.	0 °C
Priemer	60 mm
Temperature resistance of cable from	-40 °C
Temperature resistance of cable to	120 °C
Teplota okolia do	70 °C
Teplota okolia od	-20 °C
Trieda krytia	IP54


Standard version




Standard version
 Plain stem (without thread), SF94
 Copper alloy
 Insertion length = variable
 Stem diameter $\varnothing d = 6, 8, 8.5, 10$ mm




Rotatable connection with loose threaded connection
 SF91/SF15 M14 x 1.5, R 1/4, R 1/2, R 3/4
 Copper alloy
 Insertion length = variable
 Stem diameter $\varnothing d = 6, 8, 8.5, 10$ mm






NS 72 x 72




NS 96 x 96




Standard version




Standard version
 Plain stem (without thread), SF94
 Copper alloy
 Insertion length = variable
 Stem diameter $\varnothing d = 6, 8, 8.5, 10$ mm



Rotatable connection with loose threaded connection
 SF91/SF15 M14 x 1.5, R 1/4, R 1/2, R 3/4
 Copper alloy
 Insertion length = variable
 Stem diameter $\varnothing d = 6, 8, 8.5, 10$ mm



NS 72 x 72



NS 96 x 96

