



Dopyt



## TERMOMETRE

Séria IFC

IFC-14349092

Termometer Ø60, 0-120°C, L=1m, slät 50x8mm

- Expanzné
- Teplota -40°C až 400°C
- Ø60, Ø80, Ø100 mm
- Kapilára






### POPIS PRODUKTU



### ŠPECIFIKÁCIA

Capillary length	1000 mm
Insertion length	50 mm
Materiál kontaktnej časti	Mosadz
Materiál skla	Inertný plyn
Materiál tela	Plast
Plug diameter	8 mm
Prevádzková teplota max.	120 °C
Prevádzková teplota min.	0 °C
Priemer	60 mm
Temperature resistance of cable from	-40 °C
Temperature resistance of cable to	120 °C
Teplota okolia do	70 °C
Teplota okolia od	-20 °C
Trieda krytia	IP54


Standard version






Standard version  
 Plain stem (without thread), SF94  
 Copper alloy  
 Insertion length = variable  
 Stem diameter Dd = 6, 8, 8.5, 10 mm





Rotatable connection with loose threaded connection  
 SF91/SF19 SF14 x 1.5, R 1/4, R 1/2  
 Copper alloy  
 Insertion length = variable  
 Stem diameter Dd = 6, 8, 8.5, 10 mm



Standard version



Standard version  
 Plain stem (without thread), SF94  
 Copper alloy  
 Insertion length = variable  
 Stem diameter Dd = 6, 8, 8.5, 10 mm



Rotatable connection with loose threaded connection  
 SF91/SF19 M14 x 1.5, R 1/4, R 1/2  
 Copper alloy  
 Insertion length = variable  
 Stem diameter Dd = 6, 8, 8.5, 10 mm

