



Dopyt

TERMOČLÁNKY

Séria TC47-NT

TC47-NT

Termočlánok

- Teplota -40°C až 750°C
- K, J, K, T
- Telo nerez



POPIS PRODUKTU

ŠPECIFIKÁCIA

Prevádzková teplota max.	750 °C
Prevádzková teplota min.	-40 °C



Nozzle bolt material	Lead wire covering
<ul style="list-style-type: none"> Stainless steel Brass Others on request 	<ul style="list-style-type: none"> None Stainless steel overbraid (no tracer) Stainless steel overbraid (with tracer) Tin copper overbraid
Junction	Termination at lead end
<ul style="list-style-type: none"> Grounded (unisolated) Ungrounded (isolated) 	<ul style="list-style-type: none"> Bare ends
Nozzle bolt thread size	Standard thermo plug 2-pin (male)
<ul style="list-style-type: none"> 1/4 x 28 MS MS Others on request 	<ul style="list-style-type: none"> Miniature thermo plug 2-pin (male) Standard plug with cable clamp (male) Miniature plug with cable clamp (male)
Lead length	Lemoso plug size 1S (male)
<ul style="list-style-type: none"> 500 mm 1000 mm 1500 mm 2000 mm 2500 mm Others on request 	<ul style="list-style-type: none"> Lemoso plug size 2S (male) Screw-in plug, Binder (male) Others on request
Lead wire	Calibration type
<ul style="list-style-type: none"> Fibreglass / Fibreglass PTFE / PTFE PIVC / PIVC Kapton / Kapton Others on request 	<ul style="list-style-type: none"> J ANSI MC96.1 red ⊕ white ⊖ K ANSI MC96.1 red ⊕ yellow ⊖ T ANSI MC96.1 red ⊕ blue ⊖ J IEC 584-3 white ⊕ black ⊖ K IEC 584-3 white ⊕ green ⊖ T IEC 584-3 white ⊕ brown ⊖ J DIN 43714 blue ⊕ red ⊖ K DIN 43714 green ⊕ red ⊖ T DIN 43714 brown ⊕ red ⊖ Others on request



Nozzle bolt material	Lead wire covering
<ul style="list-style-type: none"> Stainless steel Brass Others on request 	<ul style="list-style-type: none"> None Stainless steel overbraid (no tracer) Stainless steel overbraid (with tracer) Tin copper overbraid
Junction	Termination at lead end
<ul style="list-style-type: none"> Grounded (unisolated) Ungrounded (isolated) 	<ul style="list-style-type: none"> Bare ends
Nozzle bolt thread size	Standard thermo plug 2-pin (male)
<ul style="list-style-type: none"> 1/4 x 28 MS MS Others on request 	<ul style="list-style-type: none"> Miniature thermo plug 2-pin (male) Standard plug with cable clamp (male) Miniature plug with cable clamp (male)
Lead length	Lemoso plug size 1S (male)
<ul style="list-style-type: none"> 500 mm 1000 mm 1500 mm 2000 mm 2500 mm Others on request 	<ul style="list-style-type: none"> Lemoso plug size 2S (male) Screw-in plug, Binder (male) Others on request
Lead wire	Calibration type
<ul style="list-style-type: none"> Fibreglass / Fibreglass PTFE / PTFE PIVC / PIVC Kapton / Kapton Others on request 	<ul style="list-style-type: none"> J ANSI MC96.1 red ⊕ white ⊖ K ANSI MC96.1 red ⊕ yellow ⊖ T ANSI MC96.1 red ⊕ blue ⊖ J IEC 584-3 white ⊕ black ⊖ K IEC 584-3 white ⊕ green ⊖ T IEC 584-3 white ⊕ brown ⊖ J DIN 43714 blue ⊕ red ⊖ K DIN 43714 green ⊕ red ⊖ T DIN 43714 brown ⊕ red ⊖ Others on request