



Dopyt



TERMOČLÁNKY

Séria TC47-AC

TC47-AC Termočlánok

- Teplota -40°C až 750°C
- K, J, K, T
- Telo nerez



POPIS PRODUKTU

ŠPECIFIKÁCIA

Prevádzková teplota max.

750 °C

Prevádzková teplota min.

-40 °C

Adjustable compression version

- Straight
- 45° bend
- 90° bend

Junction

- Grounded (unisolated)
- Ungrounded (isolated)

Probe diameter

- 3/16"
- 1/4"
- 3/8"
- 4 mm
- 6 mm
- 8 mm
- Others on request

Probe length

- Standard: 100 mm (4")
- Others on request

Compression fitting material

- Brass
- Stainless steel
- None

Thread size

- Thread size on request

Lead length

- 500 mm
- 1000 mm
- 1500 mm
- 2000 mm
- 2500 mm
- Others on request

Lead wire

- Fibreglass / Fibreglass
- PTFE / PTFE
- PVC / PVC
- Kapton / Kapton
- Others on request

Lead wire covering

- None
- Stainless steel overbraid (no tracer)
- Stainless steel overbraid (with tracer)
- Tin copper overbraid
- Interlocking flexible armour

Termination at lead end

- Bare ends
- Standard thermo plug 2-pin (male)
- Miniature thermo plug 2-pin (male)

Calibration type

- J ANSI MC96.1 red ⊕ white ⊖
- K ANSI MC96.1 red ⊕ yellow ⊖
- T ANSI MC96.1 red ⊕ blue ⊖
- J IEC 584-3 white ⊕ black ⊖
- K IEC 584-3 white ⊕ green ⊖
- T IEC 584-3 white ⊕ brown ⊖
- J DIN 43714 blue ⊕ red ⊖
- K DIN 43714 green ⊕ red ⊖
- T DIN 43714 brown ⊕ red ⊖
- Others on request

Adjustable compression version

- Straight
- 45° bend
- 90° bend

Junction

- Grounded (unisolated)
- Ungrounded (isolated)

Probe diameter

- 3/16"
- 1/4"
- 3/8"
- 4 mm
- 6 mm
- 8 mm
- Others on request

Probe length

- Standard: 100 mm (4")
- Others on request

Compression fitting material

- Brass
- Stainless steel
- None

Thread size

- Thread size on request

Lead length

- 500 mm
- 1000 mm
- 1500 mm
- 2000 mm
- 2500 mm
- Others on request

Lead wire

- Fibreglass / Fibreglass
- PTFE / PTFE
- PVC / PVC
- Kapton / Kapton
- Others on request

Lead wire covering

- None
- Stainless steel overbraid (no tracer)
- Stainless steel overbraid (with tracer)
- Tin copper overbraid
- Interlocking flexible armour

Termination at lead end

- Bare ends
- Standard thermo plug 2-pin (male)
- Miniature thermo plug 2-pin (male)

Calibration type

- J ANSI MC96.1 red ⊕ white ⊖
- K ANSI MC96.1 red ⊕ yellow ⊖
- T ANSI MC96.1 red ⊕ blue ⊖
- J IEC 584-3 white ⊕ black ⊖
- K IEC 584-3 white ⊕ green ⊖
- T IEC 584-3 white ⊕ brown ⊖
- J DIN 43714 blue ⊕ red ⊖
- K DIN 43714 green ⊕ red ⊖
- T DIN 43714 brown ⊕ red ⊖
- Others on request