



## EM-241C

Ovládanie jednosmerného motora

EM-241C  
EM-241C 12-24V DC 15A



- 12-48 V DC
- Limit prúdu (0,1-20 A)
- Regulácia rýchlosťi
- Ramping
- Digitálne nastavenie parametrov



### POPIS PRODUKTU

### ŠPECIFIKÁCIA

<b>Brake output</b>	Nie
<b>Change direction of rotation (CW/CCW)</b>	Áno
<b>Current limit</b>	0,1-25
<b>Current limit adjustable</b>	Áno
<b>Current setting range</b>	0.1-15 A
<b>Currenttrip autoreveice</b>	Áno
<b>Forward/Reverse</b>	Áno
<b>Functions</b>	Currenttrip autoreversing, Speed settings, Impulse/continuous mode, Joystick analog input, Softstart/stop, Potentiometer adjustable speed, RS485/Modbus, Stop at limit position, Speedregulator, Change direction of rotation (CW/CCW)
<b>Hmotnosť</b>	75 g
<b>Impulse/continuous mode</b>	Áno
<b>Joystick analog input</b>	Nie
<b>Montáž</b>	DIN lišta
<b>Napájacie napätie</b>	12 V DC, 24 V DC
<b>Parallel driver four motors</b>	Nie
<b>Parallel driver two motors</b>	Nie
<b>Peak current</b>	(5s) *30
<b>Position with potentiometer</b>	Nie

<b>Positioning</b>	Nie
<b>Potentiometer adjustable speed</b>	Áno
<b>Prevádzková teplota</b>	-40°C...+60°C
<b>PWM frequency</b>	2kHz/16kHz
<b>RS485/Modbus</b>	Nie
<b>Softstart/stop</b>	Áno
<b>Speed settings</b>	Áno
<b>Speedregulator</b>	Áno
<b>Stop at limit position</b>	Áno
<b>Supplier</b>	Electromen

