



ELEKTROMAGNET VM

Séria VM

VM20

- Udržiavacia sila bez napätia
- Vinutie triedy B (130°C)
- 100% pracovný cyklus
- Sila až 2000N
- K dispozícii špeciálne prevedenie



POPIS PRODUKTU

ŠPECIFIKÁCIA

Duty cycle	100 %
Insulation class	B(130°C)
Max. napätie DC	24 V
Total weight	40 g
Trieda krytia	IP65
Typ napätia	DC
Výkon	2,6 W

TYPE	P at 20°C (W)	Thickness of the piece to hold (mm)	Air gap (mm) ΔL			Magnetic Force Fm (N)
			0	0.1	0.2	
VM20	2.6	1	18	5	1	
		3	18	5	1	
		10	18	5	1	
VM25	4.3	1	20	7	3	
		3	23	7	4	
		10	29	10	7	
VM30	4.5	1	24	10	5	
		3	45	10	6	
		10	52	14	7	
VM40	7	1	39	29	22	
		3	108	57	29	
		10	128	58	37	
VM50	10	1	43	30	28	
		3	129	110	75	
		10	226	125	80	
VM65	14	1	44	35	25	
		3	266	203	140	
		10	374	238	145	
VM80	18	1	44	35	25	
		3	294	267	217	
		10	588	362	256	
VM100	25	1	45	35	25	
		3	299	282	252	
		10	1000	745	519	
VM150	45	1	93	75	60	
		3	415	350	320	
		10	2000	1500	1300	



TYPE	AA (G.3)	B	CB.1	D	E	F	Weight (Kg)
VM 20	20	M-3	25	5	—	40	0.04
VM 25	25	M-4	27	5	—	45	0.05
VM 30	30	M-4	28	5	—	45	0.17
VM 40	40	M-5	30	8	—	55	0.24
VM 50	50	M-5	30	8	—	65	0.44
VM 65	65	M-6	40	8	112	80	0.74
VM 80	80	M-6	50	10	147	95	1.42
VM 100	100	M-10	60	10	147	115	3.20
VM 150	150	M-10	65	15	197	165	6.80