



Dopyt

MERSEN

VALCOVÁ POISTKOVÁ VLOŽKA ATDR 600 V AC / 300 V DC CLASS CC TD

ATDR1-6/10

Valcová poistka UL/CSA 1 - 6/10 A, veľ. ATDR


- Najlepšia ochrana pre malé motory
- Charakteristika - pomalé




POPIS PRODUKTU

[English product sheet](#)

Peak Let-Thru Current Data - ATDR 1/4 Bll 30, 600 Volts AC



ATDR 1/4 Bll 30




Homologácia:

 UL Listed to Standard 248-4

 CSA Certified to Standard C22.2 No. 248.4

DC Listed to UL Standard 198L

ROZMERY



OBJEDNÁVACIE INFORMÁCIE

Objednávacie čísla	Popis	Menovitý prúd (A)	Napätie (V) AC	Vypínacia schopnosť	Balenie
ATDR1/4	W200855J	0.25	600 V AC/300 V DC	AC 200 kA / DC 100 kA	10
ATDR1/2	Q223068J	0.5			
ATDR8/10	K201397J	0.8			
ATDR1	T217275J	1			
ATDR1-1/8	Y218820J	1.125			
ATDR1-1/4	J218301J	1.25			
ATDR1-4/10	K219337J	1.4			
ATDR1-1/2	Y217785J	1.5			
ATDR1-6/10	K219866J	1.6			
ATDR1-8/10	Z222547J	1.8			
ATDR2	S212168J	2			
ATDR2-1/4	T213204J	2.25			
ATDR2-1/2	J212689J	2.5			
ATDR2-8/10	L213703J	2.8			
ATDR3	Y215232J	3			
ATDR3-2/10	J216254J	3.2			
ATDR3-1/2	C215742J	3.5			
ATDR4	V217276J	4			
ATDR4-1/2	Z217786J	4.5			
ATDR5	K218302J	5			
ATDR5-6/10	Z218821J	5.6			
ATDR6	L219338J	6			
ATDR6-1/4	L219867J	6.25			
ATDR7	A222548J	7			
ATDR7-1/2	R223069J	7.5			
ATDR8	X200856J	8			
ATDR9	Y201915J	9			
ATDR10	J201396J	10			
ATDR12	X201914J	12			
ATDR15	V211135J	15			
ATDR17-1/2	L211656J	17.5			
ATDR20	R214214J	20			
ATDR25	V214723J	25			
ATDR30	G216758J	30			

Minimálne objednávacie množstvo je jedno balenie - 10 ks.

ŠPECIFIKÁCIA

Balenie	10 ks
Breaking Capacity	200 kA
Charakteristika (CVL)	Time-Delay
Max. napätie AC	600 V
Max. napätie DC	300 V
Nominálny prúd	1,6 A
Výrobné číslo	K219866
Zhoda s normami	UL, CSA

