



Dopyt

MERSEN

## VALCOVÁ POISTKOVÁ VLOŽKA ATDR 600 V AC / 300 V DC CLASS CC TD

ATDR1/4

Valcová poistka UL/CSA 1/4 A, veľ. ATDR


- Najlepšia ochrana pre malé motory
- Charakteristika - pomalé




### POPIS PRODUKTU

[English product sheet](#)

Peak Let-Thru Current Data – ATDR 1/4 Bll 30, 600 Volts AC



ATDR 1/4 Bll 30



### Homologácia:




UL Listed to Standard 248-4



CSA Certified to Standard C22.2 No. 248.4

DC Listed to UL Standard 198L

### ROZMERY



# OBJEDNÁVACIE INFORMÁCIE

| Objednávacie čísla | Popis    | Menovitý prúd (A) | Napätie (V) AC    | Vypínacia schopnosť   | Balenie |
|--------------------|----------|-------------------|-------------------|-----------------------|---------|
| ATDR1/4            | W200855J | 0.25              | 600 V AC/300 V DC | AC 200 kA / DC 100 kA | 10      |
| ATDR1/2            | Q223068J | 0.5               |                   |                       |         |
| ATDR8/10           | K201397J | 0.8               |                   |                       |         |
| ATDR1              | T217275J | 1                 |                   |                       |         |
| ATDR1-1/8          | Y218820J | 1.125             |                   |                       |         |
| ATDR1-1/4          | J218301J | 1.25              |                   |                       |         |
| ATDR1-4/10         | K219337J | 1.4               |                   |                       |         |
| ATDR1-1/2          | Y217785J | 1.5               |                   |                       |         |
| ATDR1-6/10         | K219866J | 1.6               |                   |                       |         |
| ATDR1-8/10         | Z222547J | 1.8               |                   |                       |         |
| ATDR2              | S212168J | 2                 |                   |                       |         |
| ATDR2-1/4          | T213204J | 2.25              |                   |                       |         |
| ATDR2-1/2          | J212689J | 2.5               |                   |                       |         |
| ATDR2-8/10         | L213703J | 2.8               |                   |                       |         |
| ATDR3              | Y215232J | 3                 |                   |                       |         |
| ATDR3-2/10         | J216254J | 3.2               |                   |                       |         |
| ATDR3-1/2          | C215742J | 3.5               |                   |                       |         |
| ATDR4              | V217276J | 4                 |                   |                       |         |
| ATDR4-1/2          | Z217786J | 4.5               |                   |                       |         |
| ATDR5              | K218302J | 5                 |                   |                       |         |
| ATDR5-6/10         | Z218821J | 5.6               |                   |                       |         |
| ATDR6              | L219338J | 6                 |                   |                       |         |
| ATDR6-1/4          | L219867J | 6.25              |                   |                       |         |
| ATDR7              | A222548J | 7                 |                   |                       |         |
| ATDR7-1/2          | R223069J | 7.5               |                   |                       |         |
| ATDR8              | X200856J | 8                 |                   |                       |         |
| ATDR9              | Y201915J | 9                 |                   |                       |         |
| ATDR10             | J201396J | 10                |                   |                       |         |
| ATDR12             | X201914J | 12                |                   |                       |         |
| ATDR15             | V211135J | 15                |                   |                       |         |
| ATDR17-1/2         | L211656J | 17.5              |                   |                       |         |
| ATDR20             | R214214J | 20                |                   |                       |         |
| ATDR25             | V214723J | 25                |                   |                       |         |
| ATDR30             | G216758J | 30                |                   |                       |         |

Minimálne objednávacie množstvo je jedno balenie - 10 ks.

ŠPECIFIKÁCIA

|                       |            |
|-----------------------|------------|
| Balenie               | 10 ks      |
| Breaking Capacity     | 200 kA     |
| Charakteristika (CVL) | Time-Delay |
| Max. napätie AC       | 600 V      |
| Max. napätie DC       | 300 V      |
| Nominálny prúd        | 0,25 A     |
| Výrobné číslo         | W200855    |
| Zhoda s normami       | UL, CSA    |

