



COMAT RELECO PÄTICA PRE RELÉ SÉRIE C4



S4P

Objímka dosky s plošnými spoji pre C4 relé, 14-pin

- Označenie svoriek podľa DIN a EN
- V cene zaistovacia spona



PRODUCT DESCRIPTION

Typ	S4B	S4L, S4P, S4PO
Pre relé	C4	C4
Popis	Skrutkovacia päťica montáž na DIN lištu alebo panel	S4L: Päťica so spájkovacími okami S4P: Päťica do plošného spoja S4PO: Päťica do ploš. spoja s upevňovacími stĺpikmi
Pripojenie		
Menovitá záťaž	10 A /250 V	
Izolačné napätie medzi kontaktmi	2500 V	
Izolačné napätie kontakt/ lišta	2500 V	-
Veľkosť skrutiek	M3	-
Uťahovací moment pre pripojenie	1.2 Nm	-
Pevný vodič	4 mm ² 2x2.25 mm ²	-
Lankový vodič	22-14 AWG	-
Materiál	cicloy	
Hmotnosť	75 g	12 g
Prevádzková teplota	-20 °C až +60 °C	
Homologizácia	aktuálne informácie poskytneme na vyžiadanie	

ROZMERY

S4B	S4L, S4P, S4PO
-----	----------------

The image contains technical drawings for two types of relays. On the left, the S4B component is shown in two views: a top view and a side view. The top view shows a rectangular component with a central circular feature and dimensions 92 (width) and 38 (height). The side view shows a profile with a central circular feature and dimensions 92 (width) and 38 (height). On the right, the S4L, S4P, and S4PO components are shown in three views: a top view, a side view, and a front view. The top view shows a rectangular component with a central circular feature and dimensions 35.5 (width) and 47 (height). The side view shows a profile with a central circular feature and dimensions 35.5 (width) and 47 (height). The front view shows a rectangular component with a central circular feature and dimensions 35.5 (width) and 47 (height). The drawings also show the internal components and the mounting holes.

OBJEDNÁVACIE INFORMÁCIE

Objednávacie čísla	Popis	E-kód
S4B	Skrutkovacia päťica pre relé série C4 so sponou a popisným štítkom	E4016390
S4L	Päťica pre relé série C4 so spájovacími okami	E4016389
S4P	Päťica pre relé série C4 do plošného spoja	E4016388
S4PO	Päťica pre relé série C4 do plošného spoja s montážnymi stípkami	E4016387
S3C	Kovové spony pre relé C2/C3/C4	E4016392
S4R	Zadný držiak pre montáž na DIN lištu alebo upevnenie na panel	E4016386
S5R	Plochý držiak pre skrutkové pripevnenie k relé C4/C5	E4016402

SPECIFICATIONS

Hmotnosť	21 g
Min. spínacie napätie	250 V
Prevádzková teplota max.	60 °C
Prevádzková teplota min.	-40 °C
Teplota skladovania do	80 °C
Teplota skladovania od	-30 °C
Vypínací prúd	10 A

