



Polovod.nožová poistka, veľ. 2, 690 V 160A



Technical drawing of a rectangular metal plate. The drawing shows two views: a front view (left) and a side view (right). The front view shows a rectangle with dimensions a_1 (width), a_2 (width of the central hole), a_3 (width of the central hole), and a_4 (width of the central hole). The side view shows a rectangle with dimensions b (height), c_1 (height of the central hole), e_1 (height of the central hole), e_2 (height of the central hole), e_3 (height of the central hole), e_4 (height of the central hole), f (height of the central hole), and g (height of the central hole).

	StL 000	StL 00	uL0	StL 1-1000A	StL 1-255-355A	StL 2-1650A	StL 2-3000-500A	StL 3-250-400A	StL 3-425-800A
a1	75	125	135	135	150	150	150	150	150
a2	52	52	68	68	70	72.5	72.5	72.5	72.5
a3	49.5	49.5	61	63	63	63	63	63	63
a4	49.5	50	66	68	68	68	68	68	68
b	15	15	15	15	20	20	24	24	24
c1	35	35	35	40	40	48	48	60	60
c1	40.5	47.5	47.5	47.5	52.5	52.5	60	60	74
a2	20.8	29.5	29.5	29.5	39.5	39.5	51	51	51
u2	6	6	6	6	6	6	6	6	6
u3	9.5	9.5	9.5	9.5	9.5	9.5	12	11.5	11.5