



SPOJKA PRIAMA, ŠTANDARD, PUSH-ON

Séria 1000

1040 5/3

Spojka priama Push-on 2x 5mm


- Teplota -20°C do 80°C
- Tlak max. 20 bar
- Telo z poniklovanej mosadze



PRODUCT DESCRIPTION

SPECIFICATIONS

Balenie	10 ks
Materiál matice	Poniklovaná mosadz
Materiál tela	Poniklovaná mosadz
Materiál tesnenia	NBR
Prevádzková teplota max.	80 °C
Prevádzková teplota min.	-20 °C
Tvar tela	I
Vnútný priemer hadičky	3 mm
Vonkajší priemer hadičky	5 mm
Zhoda s normami	PED, REACH, RoHS



	1	2	L	CH
1040 4/2,7	4/2,7	4/2,7	27,5	8
1040 5/3	5/3	5/3	31,7	10
1040 6/4-5/3	6/4	5/3	32,2	12
1040 6/4	6/4	6/4	32,2	12
1040 8/6-6/4	8/6	6/4	33,5	12
1040 8/6	8/6	8/6	34,8	12
1040 10/8-6/4	10/8	6/4	35,6	14
1040 10/8-8/6	10/8	8/6	38,9	14
1040 10/8	10/8	10/8	39,0	14
1040 12/10	12/10	12/10	43,0	17
1040 15/12,5	15/12,5	15/12,5	47,8	22