



T-SPOJKA, ŠTANDARD, PUSH-ON

Séria 1000

1230 4/2.7

T-spojka Push-on 3x 4mm


- Teplota -20°C do 80°C
- Tlak max. 20 bar
- Telo z poniklovanej mosadze



PRODUCT DESCRIPTION

SPECIFICATIONS

Balenie	10 ks
Materiál matice	Poniklovaná mosadz
Materiál tela	Poniklovaná mosadz
Materiál tesnenia	NBR
Prevádzková teplota max.	80 °C
Prevádzková teplota min.	-20 °C
Tvar tela	T
Vnútorný priemer hadičky	2,7 mm
Vonkajší priemer hadičky	4 mm
Zhoda s normami	PED, REACH, RoHS



	1	2	L1	L2	CH
1230 4/2.7	4/2.7	4/2.7	38.5	19.5	8
1230 6/4	6/4	6/4	41.2	20.6	9
1230 8/6-6/4	8/6	6/4	43.8	20.6	9
1230 8/6	8/6	8/6	43.8	21.9	9
1230 10/8-6/4	10/8	6/4	51.0	20.6	11
1230 10/8-8/6	10/8	8/6	51.0	21.9	11
1230 10/8	10/8	10/8	51.0	25.5	11
1230 12/10	12/10	12/10	54.0	28.0	13
1230 15/12.5	15/12.5	15/12.5	63.0	32.5	16