



REDUKCIA PRIAMA, VONKAJŠÍ ZÁVIT

Séria ADAPTERS

2050 M5-1/8

Redukcia priama M5 - G1/8


- Teplota -20°C do 300°C
- Tlak max. 150 bar
- Telo z poniklovanej mosadze



PRODUCT DESCRIPTION

SPECIFICATIONS

Balenie	10 ks
Connection inside	G1/8
Connection outside	M5
Materiál tela	Poniklovaná mosadz
Prevádzková teplota max.	300 °C
Prevádzková teplota min.	-20 °C
Tlakový rozsah max.	150 bar
Tlakový rozsah min.	-0,99 bar
Tvar tela	I



	A	A1	B	L	CH
2050 M5-1/8	M5	1/8	4	14,5	14
2050 1/8-1/8	1/8	1/8	6	17,0	14
2050 1/8-1/4	1/8	1/4	6	20,5	17
2050 1/8-3/8	1/8	3/8	6	21,5	22
2050 1/4-1/4	1/4	1/4	8	22,5	17
2050 1/4-3/8	1/4	3/8	8	23,5	22
2050 1/4-1/2	1/4	1/2	8	26,5	26
2050 3/8-3/8	3/8	3/8	9	24,5	22
2050 3/8-1/2	3/8	1/2	9	27,5	26
2050 1/2-1/2	1/2	1/2	10	28,5	26