



## NADSTAVEC PRIAMY, VONKAJŠÍ ZÁVIT

Séria ADAPTERS

2070 1/8-1/8-22

Nástavec priamy G1/8 - 22

- Teplota -20°C do 300°C
- Tlak max. 150 bar
- Telo z poniklovanej mosadze



### POPIS PRODUKTU

### ŠPECIFIKÁCIA

|                          |                    |
|--------------------------|--------------------|
| Balenie                  | 10 ks              |
| Materiál tela            | Poniklovaná mosadz |
| Prevádzková teplota max. | 300 °C             |
| Prevádzková teplota min. | -20 °C             |
| Procesné pripojenie      | G1/8               |
| Tlakový rozsah max.      | 150 bar            |
| Tlakový rozsah min.      | -0,99 bar          |
| Tvar tela                | I                  |



|                 | A   | A1  | L  | B | CH |
|-----------------|-----|-----|----|---|----|
| 2070 1/8-1/8-22 | 1/8 | 1/8 | 22 | 6 | 14 |
| 2070 1/8-1/8-42 | 1/8 | 1/8 | 42 | 6 | 14 |
| 2070 1/4-1/4-35 | 1/4 | 1/4 | 35 | 8 | 17 |
| 2070 1/4-1/4-51 | 1/4 | 1/4 | 51 | 8 | 17 |