



REDUKCIA PRIAMA, VNÚTORNÝ ZÁVIT

Séria ADAPTERS

3010 M5-1/8

Redukcia priama M5 - G1/8


- Teplota -20°C do 300°C
- Tlak max. 150 bar
- Telo z poniklovanej mosadze



PRODUCT DESCRIPTION

SPECIFICATIONS

Balenie	10 ks
Materiál tela	Poniklovaná mosadz
Prevádzková teplota max.	300 °C
Prevádzková teplota min.	-20 °C
Procesné pripojenie	G1/8
Tlakový rozsah max.	150 bar
Tlakový rozsah min.	-0,99 bar
Tvar tela	I



	A	A1	L	CH
3010 M5-1/8	M5	1/8	13,0	14
3010 1/8-1/4	1/8	1/4	19,0	17
3010 1/8-3/8	1/8	3/8	20,0	22
3010 1/8-1/2	1/8	1/2	24,0	24
3010 1/4-3/8	1/4	3/8	23,0	22
3010 1/4-1/2	1/4	1/2	25,0	24
3010 3/8-1/2	3/8	1/2	27,5	24
3010 1/2-1	1/2	1	39,0	40
3010 1/2-3/4	1/2	3/4	30,0	30
3010 3/4-1	3/4	1	41,0	40