



SOLENOIDOVÝ AKTUÁTOR ERC

Séria ERC

ERC25-04/CC

- Funkcia push/pull s voliteľnou pružinou
- Vinutie triedy B (130°C)
- Pracovný cyklus 0-100%
- Sila až 191N
- K dispozícii špeciálne prevedenie



PRODUCT DESCRIPTION

SPECIFICATIONS

Absorbed power @ 20°C, 100% duty	6,3 W
Absorbed power @ 20°C, 15% duty	40,3 W
Absorbed power @ 20°C, 25% duty	24,7 W
Absorbed power @ 20°C, 40% duty	15,2 W
Absorbed power @ 20°C, 5% duty	123 W
Beginning of stroke force at 100% duty	4,4 N
Beginning of stroke force at 15% duty	14 N
Beginning of stroke force at 25% duty	10,6 N
Beginning of stroke force at 40% duty	8,2 N
Beginning of stroke force at 5% duty	23 N
End of stroke force at 100% duty	12,4 N
End of stroke force at 15% duty	25,4 N
End of stroke force at 25% duty	20,6 N
End of stroke force at 40% duty	17,6 N
End of stroke force at 5% duty	36,8 N
Insulation class	B(130°C)
Max. napätie AC	230 V
Max. napätie DC	205 V
Min. napätie AC	110 V

Min. napätie DC	6 V
Spring return	Áno
Total weight	110 g
Trieda krytia	IP00
Typ napätia	AC, DC
Zdvih	4 mm

