



SOLENOIDOVÝ AKTUÁTOR ECH

Séria ECH

ECH40-10

- Funkcia push/pull s voliteľnou pružinou
- Vinutie triedy B (130°C)
- Pracovný cyklus 0-100%
- Sila až 2800N
- K dispozícii špeciálne prevedenie




PRODUCT DESCRIPTION

SPECIFICATIONS

Absorbed power @ 20°C, 100% duty	13 W
Absorbed power @ 20°C, 15% duty	75 W
Absorbed power @ 20°C, 25% duty	45 W
Absorbed power @ 20°C, 40% duty	30 W
Absorbed power @ 20°C, 5% duty	210 W
Beginning of stroke force at 100% duty	9,5 N
Beginning of stroke force at 15% duty	30 N
Beginning of stroke force at 25% duty	23 N
Beginning of stroke force at 40% duty	18 N
Beginning of stroke force at 5% duty	50 N
End of stroke force at 100% duty	10,4 N
End of stroke force at 15% duty	27 N
End of stroke force at 25% duty	19,5 N
End of stroke force at 40% duty	16 N
End of stroke force at 5% duty	43 N
Insulation class	B(130°C)
IP class of solenoid body and connector	IP40
IP class of solenoid mounting face	IP65
Max. napätie AC	230 V

Max. napätie DC	205 V
Min. napätie AC	110 V
Min. napätie DC	6 V
Total weight	250 g
Typ napätia	AC, DC
Zdvih	10 mm



Duty-cycle ED%	Standard voltages							Under demand voltages			
	VDC							VAC		VDC	
	6	12	24	48	100	125	205	110	230	Min	Max
100%	o	o	o	o	o	o	o	o	o	4	250
40%	o	o	o	o	o	o	o	o	o	6	250
25%	x	o	o	o	o	o	o	o	o	9	250
15%	x	o	o	o	o	o	o	o	o	10	250
5%	x	o	o	o	o	o	o	x	x	12	250

Layout: o = Available ; x = Unavailable

