



SOLENOIDOVÝ AKTUÁTOR ECR

Séria ECR

ECR40-07

- Rovnaká sila v oboch smeroch
- Vinutie triedy B (130°C)
- Dvojitá cievka
- Sila až 837N
- K dispozícii špeciálne prevedenie




PRODUCT DESCRIPTION

SPECIFICATIONS

Absorbed power @ 20°C, 100% duty	13 W
Absorbed power @ 20°C, 15% duty	75 W
Absorbed power @ 20°C, 25% duty	45 W
Absorbed power @ 20°C, 40% duty	30 W
Absorbed power @ 20°C, 5% duty	210 W
Beginning of stroke force at 100% duty	10 N
Beginning of stroke force at 15% duty	28 N
Beginning of stroke force at 25% duty	22 N
Beginning of stroke force at 40% duty	17,9 N
Beginning of stroke force at 5% duty	46 N
End of stroke force at 100% duty	10,4 N
End of stroke force at 15% duty	27 N
End of stroke force at 25% duty	19,6 N
End of stroke force at 40% duty	16 N
End of stroke force at 5% duty	43 N
Insulation class	B(130°C)
Max. napätie DC	205 V
Min. napätie DC	6 V
Spring return	Nie

Total weight	800 g
Trieda krytia	IP40
Typ napätia	DC
Zdvih	7 mm



Duty-cycle ED%	Standard voltages							Under demand voltages			
	VDC							VDC		VAC	
	6	12	24	48	100	125	205	110	230	Min	Max
100%	o	o	o	o	o	o	o	x	x	5	250
40%	o	o	o	o	o	o	o	x	x	6	250
25%	x	o	o	o	o	o	o	x	x	9	250
15%	x	o	o	o	o	o	o	x	x	9	250
5%	x	o	o	o	o	o	o	x	x	12	250

Lay out: o = Available ; x = Unavailable

