



SNÍMAČE TEPLOTY

Séria TFT35

TFT35-14264042

M12x1 4-20mA 2-wire 0-50°C 50x6mm G1/2"



- Výstup 4-20mA, 0-10V
- Teplota -50 až 200°C
- Pripojenie G, M, NPT
- Médiá voda, plyny, oleje



PRODUCT DESCRIPTION

SPECIFICATIONS

Connection	G1/2
Insertion length	50 mm
Materiál kontaktnej časti	Nerezová oceľ
Materiál tela	Nerezová oceľ
Napájacie napätie DC max.	30 V DC
Napájacie napätie DC min.	10 V DC
Plug diameter	6 mm
Teplota média do	50 °C
Teplota média od	0 °C
Teplota okolia do	85 °C
Teplota okolia od	-40 °C
Tlaková odolnosť max	50 bar
Trieda krytia	IP65

Angular connector
DIN EN 17531-803

Circular connector
M12 x 1

With neck tube

With compression
fitting

Without process
connection

Technical drawings showing five types of connectors with dimensions:

- Angular connector DIN EN 17531-803:** Dimensions include $\pm 0,5$, $\varnothing 7$, 15 , and $\varnothing 1$.
- Circular connector M12 x 1:** Dimensions include 15 and $\varnothing 1$.
- With neck tube:** Dimensions include 15 and $\varnothing 1$.
- With compression fitting:** Dimensions include 15 and $\varnothing 1$.
- Without process connection:** Dimensions include 15 and $\varnothing 1$.

- Circular connector M12 x 1