



Dopyt



TERMOČLÁNKY

Séria TC47-MT

TC47-MT

Termočlánok

- Teplota -40°C až 750°C
- K, J, K, T
- Telo nerez



POPIS PRODUKTU

ŠPECIFIKÁCIA

Prevádzková teplota max. 750 °C

Prevádzková teplota min. -40 °C

Manifold block ■ Stainless steel ■ Others on request		Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour	
Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)		Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male)	
Tip diameter (Ø) ■ 4 mm ■ Others on request		Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male)	
Tip length ■ 12 mm ■ 20 mm ■ 25 mm ■ Others on request		Lemosa plug size 15 (male) ■ Lemosa plug size 25 (male)	
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request		Screw-in plug, Binder (male) ■ Others on request	
Lead wire ■ Fibreglass / Fiberglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request		Calibration type ■ J ANSI MC96.1 red Ø white Ø ■ F ANSI MC96.1 red Ø yellow Ø ■ T ANSI MC96.1 red Ø blue Ø ■ J IEC 584-3 white Ø black Ø ■ K IEC 584-3 white Ø green Ø ■ T IEC 584-3 white Ø brown Ø ■ J DIN 43714 blue Ø red Ø ■ K DIN 43714 green Ø red Ø ■ T DIN 43714 brown Ø red Ø ■ Others on request	