



Dopyt



TERMOČLÁNKY

Séria TC47-AC

TC47-AC
Termočlánek

- Teplota -40°C až 750°C
- K, J, K, T
- Telo nerez



POPIS PRODUKTU

ŠPECIFIKÁCIA

Prevádzková teplota max. 750 °C

Prevádzková teplota min. -40 °C

Adjustable compression version ■ Straight ■ 45° bend ■ 90° bend		Lead wire ■ Fibreglass / Fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request																																								
Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)		Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour																																								
Probe diameter ■ 3/16" ■ 1/4" ■ 3/8" ■ 4 mm ■ 6 mm ■ 8 mm ■ Others on request		Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male)																																								
Probe length ■ Standard: 100 mm (4") ■ Others on request		■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 15 (male) ■ Lemosa plug size 25 (male)																																								
Compression fitting material ■ Brass ■ Stainless steel ■ None		■ Screw-in plug, Binder (male) ■ Others on request																																								
Thread size ■ Thread size on request		Calibration type <table><tr><td>■ J</td><td>ANSI MC96.1</td><td>red ⊕</td><td>white ⊖</td></tr><tr><td>■ K</td><td>ANSI MC96.1</td><td>red ⊕</td><td>yellow ⊖</td></tr><tr><td>■ T</td><td>ANSI MC96.1</td><td>red ⊕</td><td>blue ⊖</td></tr><tr><td>■ J</td><td>IEC 584-3</td><td>white ⊕</td><td>black ⊖</td></tr><tr><td>■ K</td><td>IEC 584-3</td><td>white ⊕</td><td>green ⊖</td></tr><tr><td>■ T</td><td>IEC 584-3</td><td>white ⊕</td><td>brown ⊖</td></tr><tr><td>■ J</td><td>DIN 43714</td><td>blue ⊕</td><td>red ⊖</td></tr><tr><td>■ K</td><td>DIN 43714</td><td>green ⊕</td><td>red ⊖</td></tr><tr><td>■ T</td><td>DIN 43714</td><td>brown ⊕</td><td>red ⊖</td></tr><tr><td>■ Others on request</td><td></td><td></td><td></td></tr></table>	■ J	ANSI MC96.1	red ⊕	white ⊖	■ K	ANSI MC96.1	red ⊕	yellow ⊖	■ T	ANSI MC96.1	red ⊕	blue ⊖	■ J	IEC 584-3	white ⊕	black ⊖	■ K	IEC 584-3	white ⊕	green ⊖	■ T	IEC 584-3	white ⊕	brown ⊖	■ J	DIN 43714	blue ⊕	red ⊖	■ K	DIN 43714	green ⊕	red ⊖	■ T	DIN 43714	brown ⊕	red ⊖	■ Others on request			
■ J	ANSI MC96.1	red ⊕	white ⊖																																							
■ K	ANSI MC96.1	red ⊕	yellow ⊖																																							
■ T	ANSI MC96.1	red ⊕	blue ⊖																																							
■ J	IEC 584-3	white ⊕	black ⊖																																							
■ K	IEC 584-3	white ⊕	green ⊖																																							
■ T	IEC 584-3	white ⊕	brown ⊖																																							
■ J	DIN 43714	blue ⊕	red ⊖																																							
■ K	DIN 43714	green ⊕	red ⊖																																							
■ T	DIN 43714	brown ⊕	red ⊖																																							
■ Others on request																																										
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request																																										